

Silicon PNP Power Transistors

2SA1051

DESCRIPTION


- With TO-3 package
- High transition frequency
- Excellent safe operating area

APPLICATIONS

- For audio and general purpose power amplifier applications

PINNING(see Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector

Absolute maximum ratings($T_a = \text{ }^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-150	V
V_{CEO}	Collector-emitter voltage	Open base	-150	V
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current		-15	A
I_B	Base current		-1.5	A
P_C	Collector power dissipation	$T_C = 25$	150	W
T_j	Junction temperature		175	
T_{stg}	Storage temperature		-55~200	

Silicon PNP Power Transistors

2SA1051

CHARACTERISTICS


T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =-25mA ; I _B =0	-150			V
V _{(BR)CBO}	Collector-base breakdown voltage	I _C =-1mA ; I _E =0	-150			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =-1mA ; I _C =0	-5			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =-10A ; I _B =-1A			-3.0	V
V _{BE}	Base-emitter on voltage	I _C =-8A ; V _{CE} =-5V			-1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =-140V ; I _E =0			-10	μ A
I _{EBO}	Emitter cut-off current	V _{EB} =-5V ; I _C =0			-10	μ A
h _{FE-1}	DC current gain	I _C =-1A ; V _{CE} =-5V	55		160	
h _{FE-2}	DC current gain	I _C =-8A ; V _{CE} =-5V	35			
f _T	Transition frequency	I _C =-1A ; V _{CE} =-10V		60		MHz

Silicon PNP Power Transistors

2SA1051

PACKAGE OUTLINE

Fig.2 outline dimensions (unindicated tolerance: $\pm 0.1\text{mm}$)