

Silicon Power Transistors

2SD1588

DESCRIPTION

- With TO-220Fa package
- Complement to type 2SB1097
- Low speed switching

APPLICATIONS

- For low frequency power amplifier applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	emitter




Fig.1 simplified outline (TO-220Fa) and symbol

ABSOLUTE MAXIMUM RATINGS AT Tc=25

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	100	V
V _{CEO}	Collector-emitter voltage	Open base	60	V
V _{EBO}	Emitter-base voltage	Open collector	7	V
I _C	Collector current (DC)		7	A
I _{CM}	Collector current-Peak		15	A
I _B	Base current		3.5	A
P _C	Collector power dissipation	T _c =25	30	W
P _C	Collector power dissipation	T _a =25	2	W
T _j	Junction temperature		150	
T _{stg}	Storage temperature		-55~150	

Silicon Power Transistors

2SD1588

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO}	Collector-emitter voltage	I _C =50mA, I _B =0	60			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =5A I _B =0.5A			0.5	V
V _{BEsat}	Emitter-base saturation voltage	I _C =5A I _B =0.5A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =80V I _E =0			10	μA
I _{EBO}	Emitter cut-off current	V _{EB} =5V; I _C =0			10	μA
h _{FE-1}	DC current gain	I _C =3A ; V _{CE} =1V	40		200	
h _{FE-2}	DC current gain	I _C =5A ; V _{CE} =1V	20			


◆ h_{FE-1} Classifications

R	O	Y
40-80	60-120	100-200

Silicon Power Transistors

2SD1588

PACKAGE OUTLINE

Fig.2 Outline dimensions (unindicated tolerance: ± 0.15 mm)